










# Rocker Switch PJS-608 Series

## SPECIFICATIONS


1. Rating: 10A, 125/ 250VAC(UL, CSA)  
16A, 250VAC (VDE)
2. Contact resistance: 20mΩ Max.
3. Insulation resistance: 100MΩ Min. at 500VDC
4. Dielectric strength: 1,500VAC for 1 minute

## PART NUMBERING SYSTEM




{1}	PJS	—	{2}	608	{3}		{4}		{5}		{6}	Rocker / Housing	{7}	
{1} Series: PJS: Rocker switch														
{2} Model: 608														
{3} Mounting hole: R: 22x28mm, F: 22x30mm														
{4} Circuit: A: 4P ON-OFF      C: 6P ON-OFF-ON      G: 6P (ON)-OFF-(ON) B: 6P ON-ON                  D: 4P (ON)-OFF                  H: 6P ON-OFF-(ON) BL: 6P illuminated        F: 6P (ON)-ON                  AL: 4P illuminated														
{5} Rocker: 0:  1: 														
{6} Color: B: Black, G: Green, H: Gray, I: Ivory, R: Red, W: White, Y: Yellow														
{7} Stamp: 1:  2:  3:  4:  5:  6:  7: 														

## DIMENSIONS (Unit:mm)


### PJS-608R



W	PANEL THICKNESS
28.0	0.75~1.25
28.2	1.25~2.00
28.5	2.00~3.00



### PJS-608F



W	PANEL THICKNESS
30.0	0.75~1.25
30.2	1.25~2.00
30.5	2.00~3.00

